## **EKF 711 E UD**








## ELECTRONIC COMBI OVEN

Baked pasta, roasted meat and fish, chickens: your dishes will be always cooked evenly, with the highest exaltation of flavors. Efficient and compact, this oven is also suitable for delicate dishes, such as desserts for restaurants and meats that require slow cooking. Cooking is made even more precise thanks to the predisposition for the core probe, indispensable ally for the demanding chef who is always rise to the occasion. The digital display with 99 storable programs and 4 cooking steps allows you to select at any time your favorite recipe in an easy and intuitive way.









DIMENSIONAL FEATURES
----------------------

Oven dimensions (WxDxH mm)	932	926	824
Oven weight (kg)	96,2		
Distance between rack rails (mm)	68		

ELECTRICAL FEATURES			
Power supply (kW)	8,4		
Frequency (Hz)	50/60		
Voltage (Volt)	AC 380/400 3N		
N° of motors	2 Bidirectional		
Boiler	/		
Protection against water	IPX3		

EQUIPMENT				
Cardboard box dimensions with pallet (WxDxH mm)	1000	990	990	
Lateral supports	1 right + 1 left			
Cable	Three-phase + neutral [5G 2,5] L=1600 mm			
Pc serial port				
Manual + automatic washing set up				
Plug for core probe				
Removable drip box				
PLUS				
Stainless steel cooking chamber				
Stainless steel cooking chamber				
Stainless steel cooking chamber Door with inspectionable glass				
Door with inspectionable glass				
Door with inspectionable glass Adjustable door hinges				
Door with inspectionable glass Adjustable door hinges Quick fastening of lateral supports				
Door with inspectionable glass Adjustable door hinges Quick fastening of lateral supports Embedded gasket				
Door with inspectionable glass Adjustable door hinges Quick fastening of lateral supports Embedded gasket Stackable				
Door with inspectionable glass Adjustable door hinges Quick fastening of lateral supports Embedded gasket Stackable Forced cooling system of inner parts				
Door with inspectionable glass Adjustable door hinges Quick fastening of lateral supports Embedded gasket Stackable Forced cooling system of inner parts IPX 3				

FUNCTIONAL FEATURES		
Power	Electricity	
Capacity	N° 7 trays/grids 1/1 GN	
Type of cooking	Ventilated	
Steam	Direct steam controlled by knob with display (10 levels)	
Cooking chamber	AISI 304 Stainless steel	
Temperature	50 ÷ 270℃	
Temperature control	Digital probe thermometer	
Control panel	Electronic – left side	
N° of programs	99	
Programmable cooking steps	4	
Pre-heating temperature	/	
Pre-heating function	Programmable	
Door	Right side opening Ventilated Inspectionable glass	
Modularity	Available	
Feet	Not Adjustable	
OPTIONAL		
Kit for overlapping ovens	Cod. EKKM6	
Chromed grid 1/1 GN	Cod. KG9G	
AISI 304 vertical chicken co- oking pan	Cod. KGP	
Fat drip pan for chicken grids	Cod. EKT11RG	
AlSI 304 tray 1/1 GN (530x325x40mm)	Cod. KT9G	
Table	Cod. EKT 711 - Cod. EKTR 711 Cod. EKTS 711 - Cod. EKTRS 711 Cod. EKT 711 D	
	Cod. EKKC6	
Condensation hood	Cod. EKKC6	
Condensation hood Air reducer	Cod. EKKC6 Cod. EKRPA/A	
Air reducer	Cod. EKRPA/A	
Air reducer Core probe	Cod. EKRPA/A Cod. EKSC	
Air reducer Core probe Core probe with support	Cod. EKRPA/A Cod. EKSC Cod. EKSCS	
Air reducer Core probe Core probe with support Self-cleaning automatic system	Cod. EKRPA/A Cod. EKSC Cod. EKSCS Cod. KWT/A	



